


iSolution Stage series, Stage Media Mover (SMM-50) and Stage AD Mover (SAM-50), are best fixtures for lighting advertisement and showcase effect. Media Mover connects TV, projector and speaker with jointer turning at different speed and directions horizontally. AD Mover connects curtain, poster and banner as previous mechanism. Stage series made more opportunities to demonstrate. It is an ideal application in stage, show exhibition, theater and other venues.



SMM-50



Stage Media Mover

Control

- DMX 512 control channels: 5
- Controlled by any universal DMX controller
- Easy to read display for setting and addressing rapidly
- User friendly jog-wheel for prompt setup and monitor the status
- Hanger's power on/off remotely by machine display or linked DMX controller
- 5-pin BNC connector input & output are available (R, G, B, H, V)
- Comes with audio input & output
- DMX in/out: 3-pin XLR plug

iSolution

- Remote DMX addressing (RDA) can be set remotely by CA-T DMX Tester or any universal DMX controller
- Consistent DMX configuration enables Stage series to be linked with others Stage Mover

Pre-programmed function

- Manual switching between Stand Alone and DMX mode avoiding incident in public
- Built-in moving patterns for instant scenes setting
- Setting and memorizing on machine screen by manual are available
- Master unit can be linked up to 10 sets of slaves and setting each unit by master
- Single or varied units in series display by memory are available
- Each pattern can save 6 scenes with different 16 speeds and interval time (0.1s~25.5s)

Pan movement

- Pan: 360°
- Pan resolution: 16-bit
- Setting micro Pan resolution: from 0 ~ 255 steps in 1.43°
- Automatic Pan correction
- Enabling the hanger displaying and rotating with different speed and direction
- Selectable preset angle for Pan movement: 90°, 180°, 270° and 360°
- Use ultra smooth micro stepping motors

Marco

- 8 moving patterns for instant show
- Pan moving angle are selectable (30°, 45°, 60°, 90°, 120°, 180°, 270° & 360°)

Rigging

- Enabling poster plate, curtain, TV, projector or lighting to linked
- SMM-50 on the ceiling, wall or truss to demonstration
- Mounting fixture by brackets and safety cable
- Looking and adjust with Omega clamps by hand
- Displaying on the floor is available too

Construction

- Max loading capacity: 50 kg
- Ultra silent fan ideal for different applications

Specifications

- Power: 120V~60Hz / 230V~60Hz
- Size: 479 x 522 x 222 mm
- Weight: 17.4 kg

DMX512 Configuration				
Ch1	Ch2	Ch3	Ch4	Ch5
Pan Position	Pan Fine	Pan Macro	Pan Speed	Reset/Power on/off
255 — 360° 0 — 0°	255 — 16 BIT 0 —	232 ~ 255 — Marco 360° 209 ~ 231 — Marco 270° 186 ~ 208 — Marco 180° 163 ~ 185 — Marco 120° 140 ~ 162 — Marco 90° 116 ~ 139 — Marco 60° 093 ~ 115 — Marco 45° 070 ~ 092 — Marco 30° 000 ~ 069 — Index	255 — Slow Fast	255 — 0~239 — Power off 0~230 — 0~209 — Reset 0~200 — 0~139 — Power on 0~130 —

